
Authorizations descriptor

The authorization descriptor is an XML describing the different authorizations that can be granted to users.

This file should be located at `/com/soffid/addon/authorization.xml`

The template for this file is:

```
<?xml version="1.0" encoding="utf-8"?>
<autoritzacions>
  <autoritzacio>
    <!-- Required: authorization name -->
    <codi>addon:privacy:create</codi>
    <!-- Required: Functional area description -->
    <ambit>Privacy</codi>
    <!-- Required: authorization full description -->
    <descripcio>Create privacy records</descripcio>

    <!-- Optional: scope of the authorization. It can contain a comma separated list of -->
    <!-- GRUP => Group scoped role -->
    <!-- APLICACIONES => Information system scoped role -->
    <tipusDomini>GRUPS</tipusDomini>
    <!-- Optional: how the authorization will spread along business units -->
    <!-- children => the permission will be effective on business unit and its children -->
    <!-- parent  => the permission will be effective on business unit and its parents -->
    <!-- both   => the permission will be effective on business units, its parents and its children -->
    <scope>children</scope>
    <!-- Permissions that will be granted to anyone with this permission -->
    <hereta>
      user:query,
      group:query
    </hereta>
  </autoritzacio>
  ...
</autortizacions>
```

Revision #2

Created 1 June 2021 06:56:14 by pgarcia@soffid.com

Updated 1 June 2021 09:31:45 by pgarcia@soffid.com