Authorizations descriptor

The authorization descriptor is an XML describing the different authorizations that can be granted to users.

This file should be located at /com/soffid/addon/authorization.xml

The template for this file is:

```
<?xml version="1.0" encoding="utf-8"?>
<autoritzacions>
 <autoritzacio>
            <!-- Required: authorization name -->
      <codi>addon:privacy:create</codi>
            <!-- Required: Functional area description -->
      <ambit>Privacy</codi>
            <!-- Required: authorization full description -->
      <descripcio>Create privacy records</descripcio>

            <!-- Optional: scope of the authorization. It can contain a comma separated list of -->
            <!-- GRUP => Group scoped role -->
            <!-- APLICACIONS => Information system scoped role -->
      <tipusDomini>GRUPS</tipusDomini>
            <!-- Optional: how the authorization will spread along business units -->
            <!-- children => the permission will be effective on business unit and its children -->
            <!-- parent   => the permission will be effective on business unit and its parents -->
            <!-- both     => the permission will be effective on business units, its parents and its children -->
      <scope>children</scope>
            <!-- Permissions that will be granted to anyone with this permission -->
      <hereta>
         user:query,
         group:query
      </hereta>
   </autoritzacio>
   ...
</autortizacions>
```

Revision #2
Created 1 June 2021 06:56:14
Updated 1 June 2021 09:31:45