
Windows Connector

Introduction

Description

This connector implements the LDAPS protocol and it is used to connect the Sync-Server with every server that allows this communication protocol.

Managed System

This connector has been performed to connect to the Active Directory system, it's a fork of our LDAP Connector with custom features.

For more information to check if your system may be synchronized with this connector you do not hesitate to contact us through our [Contact form](#)

Prerequisites

To enable LDAPS in your Active Directory, please read the following guide: [SSL access to Active Directory](#).

It is needed an Active Directory user with full administrator access.

Download and Install

This addon is located in the Connectors section and its name is **Windows (including Active Directory)**.

For more information about the installation process you can visit the [Addons Getting started](#) page.

Agent Configuration

Basic

Generic parameters

After the installation of the addon, you may create and configure agent instances.

This addon has 5 available agents:

- Active Directory
- Active Directory Only Passwords
- Simple Windows Agent

For more information about how you may configure the generic parameters of the agent, see the following link: [Agents configuration](#)

Custom parameters

Below there are the specific parameters for this agent implementation, "Active Directory"

- Host name of the domain controller.
- Active Directory distinguished name in X500 format. e.g.: dc=soffid,dc=local
- Administrator principal name in X500 format, relative to A.D name. e.g.:
cn=Administrator,cn=Users
- Administrator password

Parameter	Description
Hostname	Host name of the server
LDAP base DN	LDAP Base name
Principal name	User name in DN format, including base name if needed
Password	Password for the user to connect.

Parameter	Description
Enable debug	Two options: [Yes / No]. When it is enabled more log traces are printed in the Synchronization Server log
Accepted certificates	Two options: [Only trusted certificates / Any (insecure)]
Follow referrals	Two options: [Don't / Yes] If you select the Yes option, Soffid could follow the references to other systems if Soffid has the proper permissions.
Manage child domains	Two options: [No / Yes] If you select the Yes option, Soffid will manage the domain referrals.
Create OUs when needed	Two options: [No / Yes] If you select the Yes option and the OUs do not exist, these OUs will be created in the Active Directory.
Real time load last login attribute	Two options: [No / Yes]
Real time load identity changes	Two options: [No / Yes] You can check this option to synchronize the identities when Soffid is the authoritative data source. You must enable periodic synchronization.

Attribute mapping

Active Directory connector could manage Users and Groups by using LDAPS protocol.

Properties

Some agents require to configure some custom attributes, you will use the properties section to do that.

To enable it, add the following properties to each object mapping:

Property	Description
rename	AD agent will always map account and group names to the SAMAccount attribute. BaseDN and cn can be calculated based on user attributes. AD agent is able to move and rename AD objects. If you don't desire users or groups to be renamed or moved, an object property named " rename " with the value " false " can be added to some object mappings.

Property	Description
searchBase	You can configure it if you want the reconciliation process to search accounts on a directory subtree other than AD root, put a searchBase property with the relative tree to look for.
key	The AD attribute works as the primary key. Usually, it's the sAMAccountName and can be omitted.
createDisabledAccounts	Set to true if you want the connector to create disabled accounts in the active directory. By default, disabled accounts are not created until enabled.

For instance:

Property	Value	+
rename	true	—
searchBase	OU="Soffid"	—

Attributes

You can customize attribute mappings, you only need to select system objects and the Soffid objects related, manage their attributes, and make either inbound or outbound attribute mappings.

Using a windows connector you can map users, groups, and role objects. Active Directory membership is automatically managed based on user and group mappings.

Any object mapping must have the following system attributes:

System attribute	Description
objectClass	Active Directory object class. The following values mostly used "user", "group" or "organizationalUnit"
baseDn	Active Directory container where user or group should be created. Its value should be absolute, containing Active Directory DC parts
relativeBaseDn	Active Directory container where user or group should be created. Its value should be relative to Active Directory DC parts.
cn	Object name

There is a bunch of AD special attributes that need some special treatment:

System attribute	Description
------------------	-------------

sAMAccountName	Is automatically mapped. It is internally mapped to role name or account name, without further customization
accountExpires	<p>Sets the last date (in nanoseconds since 1600) in which the account will be valid. A common mapping expression is:</p> <pre> if (attributes {"expirationDate"} == null) return 9223372036854775807L; else return attributes{"expirationDate"}.getTime() * 10000L + 1164455280000000000L; </pre>
samAccountType	Can be used to identify distribution lists. A value of 268435457 or 268435456 means the AD group is a distribution list group rather than a security group.
lastLogon	<p>The attribute can be used to get the last time an account was used. Soffid attribute is named lastLogin and the right mapping could be the following one. Mind when you make a reference to lastLogon attribute, every domain controller is queried about this attribute, as its value is not replicated across AD controllers:</p> <pre> if (lastLogon == null lastLogon == void) return null; Long v = Long.decode(lastLogon); v = v / 100000000L; v-=11644473600L; return new Date(v*1000); => lastLogin </pre>
userCannotChangePassword	<p>true/false</p> <p>This is a virtual attribute that can be used to indicate if a user can or cannot change the password. You can't assign this permission by directly modifying the UserAccountControl attribute.</p>

For more information about how you may configure attribute mapping, see the following link: [Soffid Attribute Mapping Reference](#)

For instance:

When this process is executed, it requests the changes to Active Directory after the **uSNChanged** .

The value of this field is saved in Soffid in the parameter **soffid.sync.authoritative.change.NAME_OF_THE_AGENT**

If you want to launch a complete load authoritative process, remove this parameter first. At the end of the process, the parameter will be generated automatically.

For more information, go to the [Soffid Parameters page](#).

Revision #30

Created 19 April 2021 15:29:26 by pgarcia@soffid.com

Updated 25 April 2024 11:22:39 by pgarcia@soffid.com