ESSO Scripting examples

1. Run an application like notepad

```
exec ("notepad.exe");
```

2. Automatic application update

```
if (SystemInfo.os == "Linux") {
  exec ("(mkdir /tmp/google-chrome-updates && " +
      " wget -O /tmp/google-chrome-updates/google-chrome-stable_current_amd64.deb " +
      " -c https://dl.google.com/linux/direct/google-chrome-stable_current_amd64.deb " +
      " && apt-get update && sudo apt-get install libappindicator1 " +
      " && sudo dpkg -i /tmp/google-chrome-updates/google-chrome-stable_current_amd64.deb " +
      " && sudo apt-get install google-chrome-stable) " +
      " </dev/null >>/var/log/google-chrome-stable_current_amd641.log 2>&1 "
      );
}
```

3.

```
<Mazinger>
  <WebApplication url="https://jira.soffid.com/.*"  >
    <Input id="login-form-username" ref-as="u"/>
    <Input id="login-form-password" ref-as="p"/>
    <Input id="login" ref-as="b"/>
    <Action event="onLoad" type="script" repeat="true" delay="5">
      account = secretStore.getAccount("soffid.org-ldap");
      debug("Account = "+account);
      u.setAttribute("value", account);
      password = secretStore.getPassword("soffid.org-ldap", account);
      debug("Password = "+password);
      p.setAttribute("value", password);
      sleep(100);
      debug("Clicking");
      b.click();
      debug("Clicked");
```

```
    </Action>
  </WebApplication>
 </Mazinger>
```