
Profiles

Description

A profile is a protocol or subset of protocols implemented by the Identity Provider. There are some accepted protocols, those allows a custom config dependent on the selected profile.

The accepted protocols are the following:

1. OpenIDProfile
2. SAML1ArtifactResolutionProfile
3. SAML1AttributeQueryProfile
4. SAML2ArtifactResolutionProfile
5. SAML2AttributeQueryProfile
6. SAML2ECPProfile
7. SAML2SSOProfile
8. CAS
9. Radius
10. Tacacs+
11. Ws-Federation
12. Shared signals & events
13. Esso

Screen overview

▼ Name
Filter
CasProfile
Esso
OpenidProfile
RadiusProfile
SAML1ArtifactResolutionProfile
SAML1AttributeQueryProfile
SAML2ArtifactResolutionProfile
SAML2AttributeQueryProfile
SAML2ECPPProfile
SAML2SSOProfile
Shared signals & events
Tacacs+Profile
Ws Federation

Displayed rows: 13

When an identity provider is created, by default, all the profiles appear disabled (the profile is displayed strikethrough). It will be necessary to config one by one depending on your company needs. To config a profile you must click on the proper profile, and Soffid will display a new window to config it.

Actions

Open profile	If you click on a row of the profile list, Soffid will display a modal window with the data and configuration of the profile selected.
--------------	--