

SAML1ArtifactResolutionProfile

Definition

Based on SAML version 1 standard. This profile is used when the Service Provider wants to resolve or check a received assertion.

Screen overview

The screenshot shows a configuration interface for the SAML1ArtifactResolutionProfile. It includes the following elements:

- Class :** A text field containing the value "SAML1ArtifactResolutionProfile".
- Enabled :** A toggle switch with three vertical bars (indicating 'Yes') and a "No" button.
- Sign Responses :** A dropdown menu with "CONDITIONAL" selected.
- Sign Assertions :** A dropdown menu with "NEVER" selected.
- Sign Requests :** A dropdown menu with "CONDITIONAL" selected.
- Apply changes :** A teal button with a document icon and the text "Apply changes".

Standard attributes

- **Class:** class name (readOnly field).
- **Enabled:** if it is checked (selected option is Yes) that protocol will be enable.
- **Sign Responses:** usually it can be set to never, as long as the assertions are signed. Its preferable to sign assertions rather than responses, because the assertion can be forwarded by the service provider to another service provider, but the response not.
- **Sign Assertions:** it's advisable to sign every assertion, so it avoids assertion spoofing. The assertion can be forwarded by the service provider to another service provider.
- **Sign Request:** the identity provider will issue requests to service providers in order to perform the single logout process. Unless it is needed by any service provider, leave it to conditional.

Revision #15

Created 14 September 2021 11:10:44 by pgarcia@soffid.com

Updated 21 June 2022 14:38:41 by pgarcia@soffid.com