

WS-Fed Example

Steps

Attribute definition

First of all, will be mandatory to create two new attributes

- User principal name
- AD SID

sofid Search ?						
<input type="checkbox"/>	Name	ShortName	Oid	OpenID name	Radius ...	Value
<input type="checkbox"/>	Filter	Filter	Filter	Filter	Filter	Filter
<input type="checkbox"/>	Full name	Fullname	urn:oid:2.16.840.1.113.30.3.1.241	full_name		
<input type="checkbox"/>	Given Name	GivenName	urn:oid:2.5.4.42	given_name		
<input type="checkbox"/>	Organizational unit	OU	urn:oid:2.5.4.11	ou		
<input type="checkbox"/>	Phone	TelephoneNumber	urn:oid:2.5.4.20	phone		
<input type="checkbox"/>	Role & group membership	memberOf	urn:oid:1.3.6.1.4.1.5923.1.5.1.1	meber_of		
<input type="checkbox"/>	Session ID	SessionId	urn:oid:1.3.6.1.4.1.22896.3.1.1	session_id		
<input type="checkbox"/>	Session key	SessionKey	urn:oid:1.3.6.1.4.1.22896.3.1.2			
<input type="checkbox"/>	Surname	Surname	urn:oid:2.5.4.4	family_name		
<input type="checkbox"/>	Birth Date	custom:birthDate	urn:oid:1.3.6.1.4.1.22896.3.1.1515	birthDate		attributes{"*birthDate"}
<input type="checkbox"/>	Cliente	custom:Cliente	urn:oid:1.3.6.1.4.1.22896.3.1.1552	Cliente		attributes{"*Cliente"}
<input type="checkbox"/>	Language	custom:language	urn:oid:1.3.6.1.4.1.22896.3.1.1518	language		attributes{"*language"}
<input type="checkbox"/>	Manager	custom:manager	urn:oid:1.3.6.1.4.1.22896.3.1.1554	manager		attributes{"*manager"}
<input type="checkbox"/>	oficina	custom:oficina	urn:oid:1.3.6.1.4.1.22896.3.1.1551	oficina		attributes{"*oficina"}
<input type="checkbox"/>	Picture	custom:picture	urn:oid:1.3.6.1.4.1.22896.3.1.1516	picture		attributes{"*picture"}
<input type="checkbox"/>	Internal id	custom:rid	urn:oid:1.3.6.1.4.1.22896.3.1.1553	rid		attributes{"*rid"}
<input checked="" type="checkbox"/>	AD SID	custom:sid	http://schemas.microsoft.com/ws/2008/06/identity/claims#primarysid	sid		attributes{"*sid"}
<input type="checkbox"/>	SSH Public key	custom:ssh_key	urn:oid:1.3.6.1.4.1.22896.3.1.1517	ssh_key		attributes{"*ssh_key"}
<input checked="" type="checkbox"/>	User principal name	custom:upn	http://schemas.xmlsoap.org/ws/2005/05/identity/claims#upn	upn		attributes{"*upn"}

Displayed rows: 23

Bear in mind, that those attributes have to be retrieved from the appropriate system:

?

[Main Menu](#) > [Administration](#) > [Configuration](#) > [Integration engine](#) > [Agents](#) 1 / 5 ▶

[Basics](#) [Integration flows](#) [Attribute mapping](#) [Load triggers](#) [Massive actions](#) [Account metadata](#)

ActiveDirectory - ActiveDirectory

System objects +

user based on user ▼

Properties

System attribute		Direction	Soffid attribute		+
objectClass		← ▼	"user"		—
givenName		↔ ▼	firstName		—
cn		→ ▼	fullName		—
sn		↔ ▼	lastName		—
relativeBaseDn		← ▼	"cn=Users"		—
department		↔ ▼	primaryGroup		—
sAMAccountName		→ ▼	userName		—
mail		↔ ▼	emailAddress		—
userPrincipalName		→ ▼	attributes{"upn"}		—
objectSid		→ ▼	attributes{"sid"}		—

Test

Triggers

And those attributes have to be defined in the object metadata:

soffid

Search

?

⚙

Main Menu > Administration > Configuration > Global Settings > Metadata
9 / 12

Object type : com.soffid.iam.api.User

Description : Builtin user object

Use textual index : Yes III

	Code	Label	Data type	Built-in type
	Filter	Filter	Filter	Filter
<input type="checkbox"/>	createdByUser	Created by	User	Yes
<input type="checkbox"/>	createdDate	Created on	Date and time	Yes
<input type="checkbox"/>	modifiedByUser	Modified by	User	Yes
<input type="checkbox"/>	modifiedDate	Modified last on	Date and time	Yes
<input type="checkbox"/>	birthDate	Birth Date	Date	No
<input type="checkbox"/>	picture	Picture	Photo	No
<input type="checkbox"/>	ssh_key	SSH Public key	String	No
<input type="checkbox"/>	language	Language	String	No
<input type="checkbox"/>	oficina	oficina	Custom object	No
<input type="checkbox"/>	Cliente	Cliente	Custom object	No
<input type="checkbox"/>	rid	Internal id	Number	No
<input type="checkbox"/>	manager	Manager	User	No
<input type="checkbox"/>	sid	AD SID	String	No
<input type="checkbox"/>	upn	User principal name	String	No

Displayed rows: 34

+

Undo Apply changes

Attribute sharing policies

Define the proper attribute policy

soffid

Search

?

⚙

Main Menu > Administration > Configuration > Web SSO > Attribute sharing policies
3 / 5

Policy : OWA

Condition Attribute requester (regex) 'Attribute requester (regex) 'https://gbr.owa.demo.soffid.net/.*'

Attributes

	Attribute	Action	Condition
	Filter	Filter	Filter
<input type="checkbox"/>	AD SID	Allow	ANY
<input type="checkbox"/>	User principal name	Allow	ANY

Displayed rows: 2

+

Undo Apply changes

Service Provider

soffid

Search

Main Menu > Administration > Configuration > Web SSO > Identity & Service providers
15 / 15

Identification

Type : WS-Federation
Identifier : https://xxx.owa.demo.soffid.net/owa/
Name : owa - ws-fed

WS-Federation

Response URL : https://xxx.owa.demo.soffid.net/owa/
Response URL

Login rules

Allow impersonations : Target application URL
UID Script : Script to compute the user name to pass to the target application
Ask for consent : No
Roles required to login : Roles required to login
System where an enabled account is required :

Undo Apply changes

Configure Exchange

Finally, you must configure the Exchange.

- 1.- Upload the SAML certificate to the certificate repository
- 2.- Search for the thumbprint of the certificate:

```
Set-Location Cert: \LocalMachine\Root; Get-ChildItem | Sort-Object Subject
```

Administrator: Windows PowerShell

```

PS Cert:\LocalMachine\Root> Set-Location Cert:\LocalMachine\Root; Get-ChildItem | Sort-Object Subject

PSParentPath: Microsoft.PowerShell.Security\Certificate::LocalMachine\Root

Thumbprint                               Subject
-----
7F88CD7223F3C813018600461A18860051385047 CN=Microsoft Authenticode(tm) Root Authority, O=MSFT, C=US
06F1AA330B927                               2 CN=Microsoft ECC Product Root Certificate Authority 2018, O=Microsoft Corporation, L=Redmond, S=W...
31F9FC8BA3805                               4 CN=Microsoft ECC TS Root Certificate Authority 2018, O=Microsoft Corporation, L=Redmond, S=Washin...
A43489159A520                               9 CN=Microsoft Root Authority, OU=Microsoft Corporation, OU=Copyright (c) 1997 Microsoft Corp.
3B1EFD3A66EA2                               5 CN=Microsoft Root Certificate Authority 2010, O=Microsoft Corporation, L=Redmond, S=Washington, C=US
8F43288AD272F                               E CN=Microsoft Root Certificate Authority 2011, O=Microsoft Corporation, L=Redmond, S=Washington, C=US
CDD4EEAE6000A                               2 CN=Microsoft Root Certificate Authority, DC=microsoft, DC=com
92B46C76E1305                               5 CN=Symantec Enterprise Mobile Root for Microsoft, O=Symantec Corporation, C=US
8E36A4562FB2E                               6 CN=Thawte Timestamping CA, OU=Thawte Certification, O=Thawte, L=Durbanville, S=Western Cape, C=ZA
18F7C1FCC3090                               5 OU="NO LIABILITY ACCEPTED, (c)97 VeriSign, Inc.", OU=VeriSign Time Stamping Service Root, OU="Ver...
4F65566336DB6                               4 OU=Class 3 Public Primary Certification Authority, O="VeriSign, Inc.", C=US
742C3192E607E                               2 OU=Class 3 Public Primary Certification Authority, O="VeriSign, Inc.", C=US
245C97DF7514E                               5 OU=Copyright (c) 1997 Microsoft Corp., OU=Microsoft Time Stamping Service Root, OU=Microsoft Corp...

PS Cert:\LocalMachine\Root>

```

- 3.- From the Exchange Management Shell, run:

```

Set-OrganizationConfig -AdfsIssuer https://gbr.idp.demo.soffid.net/profile/wsfed `
- AdfsAudienceUris
"https://gbr.owa.demo.soffid.net/owa/", "https://gbr.owa.demo.soffid.net/ecp/" `
- AdfsSignCertificateThumbprint "XXXXXXXXXXXXXXXXXXXX"

```

```
Set-OWAVirtualDirectory -Identity "OWA (Default Web Site)" -AdfsAuthentication $true `
  -BasicAuthentication $false -DigestAuthentication $false -FormsAuthentication $false `
  -WindowsAuthentication $false
```

```
Set-ECPVirtualDirectory -Identity "ECP (Default Web Site)" -AdfsAuthentication $true `
  -BasicAuthentication $false -DigestAuthentication $false -FormsAuthentication $false `
  -WindowsAuthentication $false
```

```
net stop was /y
```

```
net start w3svc
```

The server must be up to date. Otherwise WS-Fed will reject the response

Revision #8

Created 27 September 2023 06:39:31 by pgarcia@soffid.com

Updated 27 September 2023 11:30:18 by pgarcia@soffid.com