

# Step 2. Configure network discovery

The second step will be to configure the network with the proper parameter to allow you to run the discovery process.

## Step-by-step

1. First of all, you must access the network discovery page in the following path:

Main Menu > Administration > Configuration > Integration engine > Network discovery

2. Once you have accessed the network discovery page, Soffid will display all the networks created on Soffid using a list format.

3. You must select the network you want to scan to discover all its hosts.

4. Then, Soffid will display detailed information about the network. All that information will be read-only data.

5. You must click the "Enabled discovery" button to display new configuration fields, **server**, **accounts to probe**, **schedule**, and **current execution**.

6. The first of one, **Server** (from now on the **discovery proxy server**) the selected server will be used to try to connect the detected hosts using the accounts defined on the accounts to probe list. If no servers are selected, the server selected in the task definition will be used.

7. The second, **Accounts to probe** allows you to add accounts for trying to connect to the network hosts discovered.

7.1. You must click the add button (+) to add a new account.

7.2. You must select to create a new account or add an existing account.

**7.2.1.** To register a new account you must select the "Register a new account" option and fill in the login name and the password.

**7.2.2.** To use an existing account, you must select the "Use an existing account" option and select the chosen account. You have two options:

**7.2.2.1.** Writing the account name on the text field, Soffid helps you with predictive search. Then you must click the "Apply changes" to save the data and Soffid will add the account to the accounts to probe list.

**7.2.2.2.** Clicking the user icon, Soffid will show you the search account window. Once you search and find the proper account, you need to click on the account row. Then soffid will add the account to the accounts to probe list.

**8.** The third, **Schedule**: you can enable that option to schedule the execution of the task. If you enable that option, a task will be created and configured to be performed on the schedule defined.

**8.1.** You can update the schedule to be performed, the available fields are the following:

- **Month**: number of the month (1-12) when the task will be performed.
- **Day**: number of the day (1-31) when the task will be performed.
- **Hour**: hour (0-23) when the task will be performed.
- **Minute**: minute (0-59) when the task will be performed.
- **Day of week**: number of the day (0-7 where 0 means Sunday) of the week when the task will be performed.
- **Server**: (from now on **discovery manager**) primary sync server that will execute the Nmap process to discover hosts of the network. If no server is selected, Soffid will use one of the primary sync servers.

All those fields are mandatory to schedule the task.

For each value of month, day, hour, minute or day of the week:

- \* means any month, day, hour, minute or day of the week. e.g. \*/5 to schedule each five minutes.
- A single number specifies that unit value: 3
- Some comma separated numbers: 1,3,5,7
- A range of values: 1-5

**8.2.** If you update the schedule data, you will need to "Apply changes" to save the update. If there is any error, that will display and the data will not save; you must correct the data and apply changes again.

9. The fourth, the **Current execution** option allows you to fire the task execution at the current moment.

10. The **Last execution** section displays the information about the last execution of the discover network process, the start and end date and time, and the execution log.

11. The last one, **Previous executions**, will display a list with information about the previous executions. That option will be shown when the task executions were run and finished at least one time.

Soffid will display a list with information about the previous executions, the date and time when the task started, the status, and also will allow you to download the log file. To download the log file you must click on the proper "Execution log" cell, then a Txt file will be downloaded on your computer and you could check it.

# Screen overview

The screenshot displays the Soffid configuration and execution interface. It is divided into several sections:

- Configuration:** Fields for Name (lab3), Description (Laboratory network), IP Address (10.129.122.0), IP Address mask (255.255.255.0), and Server. A table for 'Accounts to probe' lists 'Login name', 'administrator', and 'soffid'.
- Schedule:** A toggle for 'Enabled' (No), a 'Task description' field (Discover network Laboratory network), and dropdowns for Month, Day, Hour, Minute, and Day of Week. The 'Server' is set to 'iam-sync.soffidnet'.
- Current execution:** A 'Start now' button.
- Last execution:** Fields for Start Date (3/7/2023 09:25), End Date (3/7/2023 10:20), and Execution log (Connecting to discovery server).
- Previous executions:** A table with columns for Start Date, Status, and Execution log. It shows two entries from 4/25/2022.

Start Date	Status	Execution log
4/25/2022 11:08	✓	T
4/25/2022 09:34	✓	T

Buttons for 'Undo' and 'Apply changes' are located at the bottom right of the 'Previous executions' section.

Revision #39

Created 23 August 2021 13:08:00

Updated 10 July 2023 14:25:47