
PAM Jump Server Installation

The purpose of this tutorial is to show how to install Jump servers and configure PAM using Docker compose, to use critical resources without knowing the password required.

Jump Server

“ A jump server, jump host or jump box is a system on a network used to access and manage devices in a separate security zone. A jump server is a hardened and monitored device that spans two dissimilar security zones and provides a controlled means of access between them. (*)

Installation

1. Execute the Store YAML

```
version: '3.8'

services:
  pam-store:
    image: soffid/pam-store:1.4.48
    environment:
      JAVA_KEYSTORE: /opt/soffid/tomee/certificates/YOUR_soffid-pam-store.jks
      KEYSTORE_PASS: YOUR_KEYSTORE
    ports:
      - "8081:8443"
    networks:
      - network
    volumes:
      - store-trustedcerts:/opt/soffid/tomee/trustedcerts
      - store-certificates:/opt/soffid/tomee/certificates
      - store-data:/opt/soffid/tomee/data
```

```
networks:
  network:
    name: YOUR_NETWORK
    driver: bridge

volumes:
  store-trustedcerts:
    name: soffid-pam-store-trustedcerts
  store-certificates:
    name: soffid-pam-certificates
  store-data:
    name: soffid-pam-store
```

Execute:

```
sudo docker compose up -d
```

2. Create a user in the Store to use it in the Launcher

Once, we are connected to the Store, we need to run a script to create the user. This script has two parameters, the user name, and the role. We have to type launcher in the role parameter.

```
docker exec YOUR_pam-store_CONTAINER /opt/soffid/tomee/bin/add-user.sh user-launcher launcher
```

Result:

```
/bin/bash: warning: setlocale: LC_ALL: cannot change locale (en_US.UTF-8)
Password: cccccc/Qul9NF1qQnDU73gYccccVHThyew7Qt8Hqpf0rEzVq1Ft7azcccccc
```

As a result of the script, we receive the password for the created user. This password will be needed later when we create the launcher container.

3. Create a user in the Store to use it in the Console

Once, we are connected to the Store, we need to run a script to create the user. This script has two parameters, the user name, and the role. We have to type console in the role parameter.

```
docker exec YOUR_pam-store_CONTAINER /opt/soffid/tomee/bin/add-user.sh user-console console
```

Result:

```
/bin/bash: warning: setlocale: LC_ALL: cannot change locale (en_US.UTF-8)
Password: asdadadasdads/QuI9NFIqQnDU73gYccccVHThyew7Qt8Hqpf0rEzVq1Ft7aadadadasd
```

As a result of the script, we receive the password for the created user. This password will be needed later when we configure PAM in the Soffid Console.

4. Execute the Launcher YAML

YAML example to create the Launcher using traefik as Ingress Controller

```
version: '3.8'

services:
  pam-launcher:
    image: soffid/pam-launcher:1.4.36
    environment:
      JAVA_KEYSTORE: /opt/soffid/tomee/certificates/YOUR_soffid-pam-launcher.jks
      KEYSTORE_PASS: YOUR_KESYSTORE
      STORE_SERVER: https://YOUR_pam-store_CONTAINER:8443
      STORE_USER: user-launcher
      STORE_PASSWORD: cccccc/QuI9NFIqQnDU73gYccccVHThyew7Qt8Hqpf0rEzVq1Ft7azccccccc
    ports:
      - "8082:8443"
    networks:
      - network
    volumes:
      - launcher-trustedcerts:/opt/soffid/tomee/trustedcerts
      - launcher-certificates:/opt/soffid/tomee/certificates
      - launcher-data:/opt/soffid/tomee/launcher
      - /var/run/docker.sock:/var/run/docker.sock
    networks:
      network:
        name: YOUR_NETWORK
```

driver: bridge

volumes:

launcher-trustedcerts:

name: soffid-pam-launcher-trustedcerts

launcher-certificates:

name: soffid-pam-certificates

launcher-data:

name: soffid-pam-launcher

Execute:

```
sudo docker compose up -d
```

5. Configure the Console



The screenshot shows the Soffid web interface. At the top, there is a search bar with the text "Buscar" and a settings icon. Below the search bar is a breadcrumb navigation path: [Menú principal](#) > [Administración](#) > [Configurar Soffid](#) > [Configuraciones de seguridad](#) > [Configurar servidores de sesión PAM](#) 1 / 1. The main content area displays a form for configuring a PAM session. The fields are: "Nombre del grupo" with value "pam-ssh-configuration-2"; "Descripción" with value "PAM configuration ssh"; "Nombre de usuario" with value "soffid.pat.lab-console-2"; "Contraseña" with a masked password and a key icon; "URL" with value "https://soffid-pam-store-2:8443"; and "Grupo servidores de salto" with value "https://soffid.pat.pam-2:8082". At the bottom right, there are two buttons: "Deshacer" and "Aplicar cambios".

Privileged Account Session Recording

Be in mind that you need to download the latest image of the required Privileged Account Session Recording that you need depending on the protocol.

- soffid-pasr-ssh
- soffid-pasr-rdp
- soffid-pasr-jdbc

- soffid-pasr-http
- soffid-pasr-https
- soffid-pasr-tn5250
- soffid-pasr-kube

Examples

Linux

```
docker pull soffid/soffid-pasr-ssh
```

Windows

```
docker pull soffid/soffid-pasr-rdp
```

To save a Web session you will need to add some parameters to the launcher system.properties (/opt/soffid/tomee/conf/system.properties)

Parameters to add:

```
SOFFID_PAM_PARAMS_http=--shm-size=1024m --privileged -eVNCSERVER=yes  
SOFFID_PAM_PARAMS_https=--shm-size=1024m --privileged -eVNCSERVER=yes
```

(*) https://en.wikipedia.org/wiki/Jump_server

Revision #11

Created 6 August 2024 13:57:47

Updated 27 September 2025 11:54:51 by Sion Vives