
SCIM MailDomain examples

Operations

This page shows the operations that can be performed for the MailDomain object.

List all

Request

```
GET http://<your-domain>/soffid/webservice/scim2/v1/MailDomain
```

Response 200 OK

```
{
  "schemas": [
    "urn:ietf:params:scim:api:messages:2.0:ListResponse"
  ],
  "totalResults": 2,
  "startIndex": 1,
  "Resources": [
    {
      "meta": {
        "location":
"http://soffid.pat.lab:8080/soffid/webservice/scim2/v1/MailDomain/523263",
        "resourceType": "MailDomain"
      },
      "schemas": [
        "urn:soffid:com:soffid:iam:api:MailDomain"
      ],
      "name": "soffid.com",
      "obsolete": false,
      "description": "Soffid",
      "id": 523263
    }
  ]
}
```

```

    },
    {
      "meta": {
        "location":
"http://soffid.pat.lab:8080/soffid/webservice/scim2/v1/MailDomain/523265",
        "resourceType": "MailDomain"
      },
      "schemas": [
        "urn:soffid:com.soffid.iam.api.MailDomain"
      ],
      "name": "soffid.org",
      "obsolete": false,
      "description": "Old Domain",
      "id": 523265
    }
  ]
}

```

List by filter

List all Mail domain with a filter expression.

It is allowed to use pagination and sort the information, for more information visit the [Sorting](#) and [Pagination](#) information.

Request

```
GET http://<your-domain>/soffid/webservice/scim2/v1/MailDomain?filter=obsolete eq false and
description co old
```

Response 200 OK

```

{
  "schemas": [
    "urn:ietf:params:scim:api:messages:2.0:ListResponse"
  ],
  "totalResults": 1,
  "startIndex": 1,

```

```
  "Resources": [
    {
      "meta": {
        "location":
"http://soffid.pat.lab:8080/soffid/webservice/scim2/v1/MailDomain/523265",
        "resourceType": "MailDomain"
      },
      "schemas": [
        "urn:soffid:com.soffid.iam.api.MailDomain"
      ],
      "name": "soffid.org",
      "obsolete": false,
      "description": "Old Domain",
      "id": 523265
    }
  ]
}
```

Query by id

Query a Mail Domain by its id (primary key).

Request

```
GET http://<your-domain>/soffid/webservice/scim2/v1/MailDomain/523263
```

Response 200 OK

```
{
  "meta": {
    "location": "http://soffid.pat.lab:8080/soffid/webservice/scim2/v1/MailDomain/523263",
    "resourceType": "MailDomain"
  },
  "schemas": [
    "urn:soffid:com.soffid.iam.api.MailDomain"
  ],
  "name": "soffid.com",
  "obsolete": false,
  "description": "Soffid",
}
```

```
"id": 523263
}
```

Create

Request

```
POST http://<your-domain>/soffid/webservice/scim2/v1/MailDomain
```

JSON

```
{
  "schemas": [
    "urn:soffid:com.soffid.iam.api.MailDomain"
  ],
  "name": "newdomain.com",
  "obsolete": false,
  "description": "New Domain"
}
```

Response 201 Created

```
{
  "meta": {
    "location":
      "http://soffid.pat.lab:8080/soffid/webservice/scim2/v1/MailDomain/1976941",
    "resourceType": "MailDomain"
  },
  "schemas": [
    "urn:soffid:com.soffid.iam.api.MailDomain"
  ],
  "name": "newdomain.com",
  "obsolete": false,
  "description": "New Domain",
  "id": 1976941
}
```

Update partial

Only attributes with changes will be updated, the other will maintain the same value.

Request

```
PATCH http://<your-domain>/soffid/webservice/scim2/v1/MailDomain/1976941
```

JSON

```
{
  "Operations": [
    {
      "op": "replace",
      "path": "description",
      "value": "New domain (xxx)"
    },
    {
      "op": "replace",
      "path": "obsolete",
      "value": "true"
    }
  ]
}
```

Response 200 OK

```
{
  "meta": {
    "location":
"http://soffid.pat.lab:8080/soffid/webservice/scim2/v1/MailDomain/1976941",
    "resourceType": "MailDomain"
  },
  "schemas": [
    "urn:soffid:com.soffid.iam.api.MailDomain"
  ],
  "name": "newdomain.com",
  "obsolete": true,
  "description": "New domain (xxx)",
  "id": 1976941
}
```

Update all

This operation replaces all values in the Mail Domain.

- Note that the attribute id is required to confirm that the resource "...MailDomain/<id>" is the same that the JSON MailDomain.
- Note that all the attributes not included in the request will be cleared in the MailDomain type and their data will be lost.
- Note that not all the attributes are updatable, for example, tag meta, avoid these tags.

For more information visit [Resource data model page](#)

Request

```
PUT http://<your-domain>/soffid/webservice/scim2/v1/MailDomain/1976941
```

JSON

```
{
  "schemas": [
    "urn:soffid:com.soffid.iam.api.MailDomain"
  ],
  "id": 1976941,
  "name": "newdomain.com",
  "obsolete": false,
  "description": "New Domain"
}
```

Response 200 OK

```
{
  "meta": {
    "location":
      "http://soffid.pat.lab:8080/soffid/webservice/scim2/v1/MailDomain/1976941",
    "resourceType": "MailDomain"
  },
  "schemas": [
    "urn:soffid:com.soffid.iam.api.MailDomain"
  ],
  "name": "newdomain.com",
  "obsolete": false,
```

```
"description": "New Domain",  
"id": 1976941  
}
```

Delete

Please note after this delete, the mail domain has to be created again to use it in the next examples.

Request

```
DELETE http://<your-omain>/soffid/webservice/scim2/v1/MailDomain/1976941
```

Response 204 No Content

```
204 No Content
```

Error response

For more information about error response visit
<https://bookstack.soffid.com/link/116#bkmrk-error-response>

Revision #9

Created 11 May 2021 11:00:42 by pgarcia@soffid.com

Updated 21 June 2023 09:32:33 by pgarcia@soffid.com