

# Custom objects

## Description

The custom objects are the objects created by the administrator to extend the Soffid underlying data model. This allows you to store additional information that is not natively supported by Soffid.

This option allows administrator users to provide objects with content.

For more information about how to create a new Custom object you can visit the [Metadata page](#).

## Screen overview

soffid

Search

?

⚙

Main Menu > Administration > Configuration > Global Settings > Metadata

◀ 12 / 12

≡

Object type :

JobPosition

Description :

Job position

Use textual index :

III

No

Public object :

Yes

III

■	Code	Label	Data type	Built-in type
	Filter	Filter	Filter	Filter
<input type="checkbox"/>	name	Name	String	Yes
<input type="checkbox"/>	description	Description	String	Yes
<input type="checkbox"/>	code	Code	String	No
<input type="checkbox"/>	location	Location	String	No

Displayed rows: 4

+

Undo

Apply changes

soffid

Search

?

⚙

[Main Menu](#) > [Administration](#) > [Resources](#) > [Custom objects](#) > Job position

Name Any

Description Any

[Quick](#) [Basic](#) [Advanced](#)

	Name	Description
<input type="checkbox"/>	IAM_Consultant	IAM Consultant
<input type="checkbox"/>	IAM_Architect	IAM Architect
<input type="checkbox"/>	IAM_Engineer	IAM Engineer

Displayed rows: 3

# Related objects

1. **Object Type:** objects created by the administrator.

# Standard attributes

- **Name:** identification name.
- **Description:** brief description.

Every single custom object could have specified attributes defined by the administrator users when they create the object type.

# Actions

## Custom object query

Query	Allows you to query custom object through different search systems, <a href="#">Quick</a> , <a href="#">Basic</a> and <a href="#">Advanced</a> .
Add or remove columns	Allows you to show and hide columns in the table.
Add new	Allows you to create a new custom object. You can choose that option on the hamburger menu or clicking the add button (+). To add a new custom object it will be mandatory to fill in the required fields

<b>Delete</b>	Allows you to remove one or more custom objects by selecting one or more records and next clicking the button with the subtraction symbol (-). To perform that action, Soffid will ask you for confirmation, you could confirm or cancel the operation.
<b>Import</b>	Allows you to upload a CSV file with the custom object list to add or update custom objects to Soffid. First, you need to pick up a CSV file, that CSV has to contain a specific configuration. Then you need to check the content to be loaded, it is allowed to choose if you want or not to load a specific attribute. And finally, you need to select the mappings for each column of the CSV file to import the data correctly and to click the Import button.
<b>Download CSV file</b>	Allows you to download a csv file with the custom objects information.

## Custom object detail

<b>Apply changes</b>	Allows you to save the data of a new custom object or to update the data of a specific custom object. To save the data it will be mandatory to fill in the required fields
<b>Undo</b>	Allows you to undo any changes made
<b>Delete</b>	Allows you to remove a custom object. You can choose that option on the trash icon. To perform that action, Soffid will ask you for confirmation, you could confirm or cancel the operation.

# Examples

## Example 1

```
... ..
ICustomObj = serviceLocator.getCustomObjectService().findCustomObjectNames("JobPosition");
... ..
```

## Example 2

```
... ..
ICustomObj = serviceLocator.getCustomObjectService().findCustomObjectByTypeAndName("JobPosition",
"IAM_Engineer");
... ..
```

## Example 3

```
... ..
ICustomObj = serviceLocator.getCustomObjectService().findCustomObjectByJsonQuery("JobPosition", "name co "
+ "\"IAM\"");
for (var i=0; i<ICustomObj.length; i++) {
    atributes = ICustomObj[i].getAttributes();
    out.println("*** Custom Object - " + i + " - " + ICustomObj[i].name);
    out.println("*** Custom Object - " + i + " - " + atributes.get("code"));
    out.println("*** Custom Object - " + i + " - " + atributes.get("location"));

    ... ..
}
... ..
```

---

Revision #6

Created 8 April 2021 10:58:51 by pgarcia@soffid.com

Updated 30 October 2024 12:05:33 by pgarcia@soffid.com